

Sterling Computer Sales, LLC

11 Laetitia Lane

Landenberg, PA 19350

Phone: 1.800.659.6708 or 610.255.0198

Fax: 610.255.3737

www.sterlingcomputersales.com

AZTEC ATX4 Model Description:

The Aztec-ATX4 lunchbox portable computer has a plastic outer shell and an inner aluminum liner. The keyboard folds in front of the display and also has an integrated touch pad. This unit features an incredible expansion capacity to hold multiple full length interface cards and has dual pentium capability. This unit is designed to accommodate a standard ATX size motherboard and has the capability to accept passive backplane boards. It is now available in a tiltable 15.4 inch 1280x1024 display. **NEW! Low Voltage Portable!** This unit is now available with a low voltage, harsh environment motherboard that consumes as little as 3 watts of power. This motherboard option is mainly for applications with limited ventilation and space constraints.



Environmental Specifications:

Oper. Temp.	0°C-50°C
Relative Humidity	20-80% (non-condensing)
Shock (operating, all axes)	15g
Vibration (operating, all axes)	1.25g @ 10-100Hz
Compliance	CE & FCC Class B Compliant, UL, cUL, CCIB

Motherboard	ATX
Slot	7
Drive Bay	2 x 5.25" 2 x 3.5"
Color	Charcoal/beige
LCD Size	14.1"-15.4" (Tiltable)
Resolution	1024x768, 1280x1024, (1400x1050 with 16MB AGP Video Only)
Video	AGP Video: ATI M3 chipset card with 16MB PCI Video: PCI D/C with 4MB Video RAM Conversion Board: Analog-to-digital conversion board **Conversion Board enables you to use your own AGP or PCI Video card**
Processors	Intel Pentium III, Pentium 4, AMD Athlon XP
Motherboard Option	NEW! Sterling Mainboard is a low voltage, Harsh Environment Motherboard. The Sterling Mainboard consumes as little as 3watts of power. This low power solution can run cool in a harsh industrial environment. For applications with limited ventilation and space constraints.
Keyboard/Mouse	108 keys, multi-languages/touchpad
Case Size	17.5" x 13.1" x 9.6" Inches
Power Supply	Full range ATX 250W with Active PFC
Case Weight	11.5kg (25.3lbs)
Speaker	Built-in amplified speaker
Carrying Case	Padded carrying case with wheels
Stabilize Bar	1
Cooling	1 x 80mm by 25mm
Case	External chassis-flame retardant ABS plastic/ internal chassis-aluminum alloy color Gold 40s
Option	Hard Shell Shipping Cases, DC Power supply

