

Sterling Computer Sales, LLC

11 Laetitia Lane

Landenberg, PA 19350

Phone: 1.800.659.6708 or 610.255.0198

Fax: 610.255.3737

www.sterlingcomputersales.com

ZEUS-A2 Model Description:

The Zeus-A2 model has a 15.4 inch LCD screen that displays 1280x1024. It is based on a well engineered all-aluminum chassis surrounded by an all aluminum outer shell with shock absorbing composite rubber corner blocks. The built-in LCD screen is protected by a 5 mm thick impact-resistant glass. The NEMA 4/12 compliant keyboard with built-in pointing device is environmentally sealed, offering protection against water, dust and accidental spills. The internal 3.5" drive bays are shock-mounted to protect the hard disk drives from damage. It provides protection to the computer unparalleled by any other chassis.



Environmental Specifications:

	Operating	Storage
Temperature	0 to 60°C	-20 to 60°C
Humidity	Meth 5%-95% RH, non-condensing	
Altitude	15,000 ft.	40,000 ft.
Shock	15g, 11ms	50g, 11ms
Vibration	20-60Hz, 0.075mm	10-50Hz, 0.15mm
Drop	3 feet height free drop	
EMI & Safety	FCC Class B, CE, UL, TUV	
Case	Hard Anodizing Surface: MIL-A-8625E Type II/III	

Motherboard	ATX	SBC	SBC
Slot	7	7	14
Drive Bay	2 x 5.25" 2 x 3.5"	3 x 5.25" 2 x 3.5"	1 x 5.25" 2 x 3.5" 1 x Slim CD Bay
Color	Black		
LCD Size	15.1", 15.4", 17.1"		
Resolution	1024x768, 1280x1024, 1280x1024		
Video	Conversion Board: Analog-to-digital conversion board **Conversion Board enables you to use your own AGP or PCI Video card**		
Processors	Intel Pentium III, Dual Intel Pentium III, Pentium 4 AMD Athlon XP		
Keyboard/Mouse	Full size mechanical key-switch keyboard Mouse touch pad with dual buttons		
Case Size	17.2"W x 13.4"H x 9.3"D		
Power Supply	300W 110/220V auto-switch power supply		
Case Weight	26lbs = SKD, 33lbs = System		
Speaker	Built-in amplified stereo speakers		
Carrying Case	Padded carrying case with wheels		
Stabilize Bar	1		
Cooling	1st Side panel fan: 6 x 6 x 25cm (Airflow 25.5 CFM) 2nd Side panel fan: 4 x 4 x 20cm (Airflow 5.7 CFM) Back cover fan: 8 x 8 x 15cm (Airflow 29.9 CFM) - SBC		
Case	Light weight aluminum chassis Rubber protected corner & drive shock-mount Air circulation fan with filter LCD brightness control & POWER/IDE LED indicator 3mm impact-resistant LCD screen glass		
Option	Hard Shell Shipping Cases, DC Power supply, water resistant keyboard		